

NEDERMAN 426E



TECHNICAL SPECIFICATION

Application	Dust, Granulate, Grit, Swarf
Certifications	CE
Dustbin Volume (l)	58 l Cyclonic Silo + 47 l Dustbin
Filter Area (m ²)	1,56 (Microfibre) 2,38 (Paper)
Filter Cleaning Method	Reverse Air Pulse
Installation	Outdoor, Indoor
Protection Class	IP44
Filter Material	Microfibre
Filter Type	Cartridge
Frequency (Hz)	50/60
Hose Diameter (mm)	51
Hose Length (m)	7,5
Max Airflow (m ³ /h)	460
Max Vacuum (kPa)	-21,5
No. of Filter Elements	1
Noise Level (dB(A))	75
Power (kW)	2,4
Power Voltage (V)	230
Type of Hose	PVC
Weight (kg)	119

DESCRIPTION

Industrial dry vacuum cleaner 426E is designed for removal and collection of industrial waste and spillage. This powerful dry vacuum suction unit comes equipped with a silo and cyclonic pre-separator before the filter, ensuring efficient collection of large quantities of material. The 426E Industrial vacuum can also be equipped with a HEPA filter for finer particles.

The industrial vacuum cleaner includes slots for handling by forklift. Special swiveling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially easy. The dry vacuum's cyclonic silo is equipped with a manual valve.

FEATURES

- Pre-separation in silo
- Manual filter cleaning prolongs the filter's lifetime
- Forklift handling

SUPPLIED WITH

426E - NEL3R:

- Cleaning set
- Scraping tool
- Conical nozzle

426E - NEL3RT

- Cleaning set
- Scraping tool
- Conical nozzle

PART CODE/ORDERING TABLE

426E - NEL3R	42442600
426E - NEL3RT	42442602

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT