

NEDERMAN 405A - DUAL CONTAINER SYSTEM



TECHNICAL SPECIFICATION

Certifications	CE
Compressed Air Requirement	3,0 Nm ³ /min
Hose Diameter (mm)	51
Hose Length (m)	7,5
Max Airflow (m ³ /h)	342
Max Vacuum (kPa)	-52
Noise Level (dB(A))	75,5
Type of Hose	PVC
Weight (kg)	119

SUPPLIED WITH

- Floor cleaning equipment

DESCRIPTION

Dual container system, designed for removal of industrial waste. This powerful industrial vacuum cleaner comes equipped with a silo and filter container for the removal of industrial waste materials. Special swiveling, locking wheels are sized to increase mobility, and make the handling of heavy loads simple.

The silo is designed to allow the collected material to be discharged over gratings or chutes for the central collection of materials. The unit can be equipped with an adjustable counterweight valve and holder for discharge into bags. The model include slots for handling by forklift.

FEATURES

- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground

PART CODE/ORDERING TABLE

405A -NE52 with floor cleaning equipment	42140500
--	----------

ACCESSORIES

Control Spneum for NE	43212001
Control S for NE 22-76	43220001
Control S for NE 22-76	43220026
Control S for NE 86-96	43222008

PERFORMANCE GRAPH

