

Datasheet Reference No: DF-SB18

Rev. 2 - April 2018

Dust and Fume Extraction

GEF CS 10/15/18 SPRAY BOOTH



FEATURES

- 2 Stage Filtration
- Low Noise, high performance fan included
- Large working area for all sizes of projects
- Ceiling light and electrical panel
- Side and roof panels

ACCESSORIES

- Ceiling Light
- Fan switch
- Fan/Light Switch
- Manual Turntable
- Automatic Turntable

MATERIALS/FINISH OPTIONS

- Painted Finish (Standard)
- Finish in galvanised sheet metal (Optional)
- Finish in stainless steel (Optional)

DESCRIPTION

The CS Spray Booth is a dry paint booth used for painting applications using chemical solvents and for water based paints.

Featuring filtration with ANDREAE paper filters and can also be supplied with a paint stop filter. The CS is supplied with supporting legs and a worktable where the is the facility to install a turntable.

The electric motor is installed on the top of the unit.

PART CODE/ORDERING TABLE

GEF CS 10 Spray Booth	DF-SB10-003
GEF CS 15 Spray Booth	DF-SB15-003
GEF CS 18 Spray Booth	DF-SB18-003

TECHNICAL SPECIFICATION

Model	Power (kW)	Airflow (m³/h)	Residual Pressure (Pa)	Dimensions (mm)	Outlet Dimensions (mm)	Extraction Area (mm)	Discharge Diameter (Ømm)		
CS 10	0.55	1800	245.16	1050 x 900 x 2250	300 x 180	990 x 900	Ø 200		
CS 15	1.1	3600	245.16	1500 x 900 x 2250	300 x 180	1440 x 900	Ø 250		
CS 18	1.1	3600	245.16	1800 x 900 x 2250	300 x 180	1740 x 900	Ø 250		

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT