

S - FUNNEL SHAPED RUBBER NOZZLE





DESCRIPTION

The S type nozzle is a soft rubber nozzle, flexible with internal grooves for better fit onto the vehicle exhaust pipe.

Available Ø80, Ø100 & Ø125 mm hose connection.

With this nozzle, scratching the vehicle and the risks of damage are reduced. The relatively soft rubber nozzle is versatile for most vehicles and comes in a range of connection sizes and configurations listed below.

OPERATION

The Nozzle is capable of fitting both exposed exhausts and those which are covered/hidden by bumpers.

The flexible nature of the rubber allows the nozzle to be pressed onto the exhaust, allowing the pipe to be sealed and the fumes can then be extracted safely.

The nozzle can be attached onto the exhaust directly and connected to a hose reel or channel duct system to achieve efficient and safe extraction.

AES can supply hose reels, channel ducting and other extraction options to suit the S-Type nozzle.

TECHNICAL SPECIFICATION/AES ORDERING TABLE

Part No.	Description	Exhaust	Hose Connection	Weight	AES Part Code
06-168	S-65/90	Ø90 mm	Ø80 mm	0.65 kg	EA-NZ03-001
06-168A	S-65/90 c/w tight damper	Ø90 mm	Ø80 mm	1.35 kg	EA-NZ03-002
06-167	S-80/130	Ø130 mm	Ø80 mm	0.80 kg	EA-NZ03-003
06-167A	S-80/130 c/w tight damper	Ø130 mm	Ø80 mm	1.50 kg	EA-NZ03-004
06-166	S-100/150	Ø150 mm	Ø100 mm	0.85 kg	EA-NZ03-005
06-166A	S-100/150 c/w tight damper	Ø150 mm	Ø100 mm	1.40 kg	EA-NZ03-006
06-169	S-100/150	Ø150 mm	Ø125 mm	0.90 kg	EA-NZ03-007
06-169A	S-100/150 c/w tight damper	Ø150 mm	Ø125 mm	1.45 kg	EA-NZ03-008

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT