

SBM - OVAL RUBBER NOZZLE WITH BELLOWS



DESCRIPTION

The SBM nozzle uses compressed air to attach to the exhaust pipe, this can be achieved by using the inflatable air bellows and a hand pump, or by connecting to a compressed air supply.

The connection can be made from a compressed air system at 1 bar.

Available in Ø100 & Ø150 mm hose connection.

The SBM is available for both passenger cars and commercial vehicles with single and dual exhaust pipes.

Versions with double bellows are available on request.

OPERATION

The SBM can be connected to the exhaust pipe in two different ways. The first uses a hand pump with vent valves can be used to inflate the bellows and secure the connection.

The second connection method uses compressed air which when set to 1 bar can suitably inflate the nozzle allowing a secure connection.

The nozzle can be attached onto the exhaust directly and connected to a hose reel or channel duct system to achieve efficient and safe extraction.

AES can supply hose reels, channel ducting and other extraction options to suit the GeoFlexGrip nozzle.

TECHNICAL SPECIFICATION/AES ORDERING TABLE

Part No.	Description	Exhaust	Hose Connection	Weight	AES Part Code
06-364A	SBM 120/40	120/40 mm	Ø80 mm	0.90 kg	EA-NZ09-001
06-364B	SBM 120/100	120/40 mm	Ø100 mm	0.90 kg	EA-NZ09-002
06-368A	SBM 200/100 (Smaller lorries with stroke bore less than 3.0 L)	200/100 mm	Ø125 mm	1.30 kg	EA-NZ09-003
06-368B	SBM 200/10	200/100 mm	Ø150 mm	1.60 kg	EA-NZ09-004

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT