

NEDERMAN HOSE REEL 886 ATEX



DESCRIPTION

The Nederman stainless steel hose reel 886 ATEX is a robust hose reel with large hose capacity for heavy duty industrial use.

This hose reel is constructed for environments where high hygiene and corrosion resistance is required.

886 ATEX hose reel in stainless steel is approved for use in zones 1, 2, 21 and 22 in accordance with ATEX 2014/34/EC, Equipment group II, Category 2G D.

TECHNICAL SPECIFICATION

Product Name	Hose Reel 886 ATEX
Connection hose length (m)	-
Type of hose	M
Media	Compressed air, water
Colour	Stainless
Diameter, connection hose (m)	19
Weight (kg)	31
Corrosion resistance	(Stainless Steel)
Electric/Spring driven	(Spring)

FEATURES

- Unique design makes easy cleaning
- Up to 25 m (82 ft.) hose capacity
- Meets international hygienic requirement
- ATEX approved

HOSE SPECIFICATION

Delivered with hose	Distribution hose length (m)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Max hose length	Part Number
Yes	25	12,5	2		30804686
No		12,5	10	25	30804786
Yes	15	19	2		30804886
No		19	7,5	20	30804986

Hose type	Specification	Temperature range, °C	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
M	Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive.	-30 - 80	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT