

RJH GRYPHON EXTRACTION-MOUNTED GRINDER



TECHNICAL SPECIFICATION

Dimensions (HxWxD)	560 x 280 x 1150 mm
Weight	50 kg
Motor	1 PH (230V) 0.7 kW 3 PH (400V) 0.85kW
Grinding Wheel Size	200mm dia. x 25mm w
Speed	2880rpm @50Hz 3450rpm @60Hz
Centre of Grinding Wheel	150 mm

DESCRIPTION

The RJH Morrisflex Gryphon extraction-mounted grinder is well known for its high performance and durability, offering multiple safety features as standard.

OPTIONAL REFINEMENTS

- Flexible halogen floodlight with transformer available
- Lockable trip pole isolator
- Lockable "E" stop
- Motor Breaking System
- Wheel Dresser

FEATURES

- 2 fitted grinding wheels
- Adjustable, non-tip cast-iron work rest
- Spark arresters
- Polycarbonate eye shields
- No-volt starter
- Cast-iron wheel guards

AES PART CODE/ORDERING TABLE

RJH Gryphon Extraction-Mounted Grinder (1PH)	WE-GM03-001
RJH Gryphon Extraction-Mounted Grinder (3PH)	WE-GM03-003

SAFETY FEATURES

- Heavy duty adjustable polycarbonate eye shields
- No-volt overload push-button starter
- Motor thermal overload protection
- 110 volt control circuit (extraction versions only)
- Full wheel guarding with 2" (approx 50mm) spigot
- Foot stop (pedestal versions only)
- Dust extractor features:
 - 0.55kw motor
 - Tray collector for easier and cleaner waste handling
 - High quality polyester needle felt filter

SAFE WORKING AREA

