

## WOODWORKING LATHE SAFETY GUARD



### TECHNICAL SPECIFICATION

Dimensions (Glass)	800 x 500 mm
Length (Frame)	1800 mm
Height (Frame)	800 mm
Weight	15 kg
Protection Screen	5 mm PETG panel

If required the guard can come fitted with its own adjustable extraction hood or adapted to suit an existing hood if available.

### DESCRIPTION

AES offer a comprehensive range of lathe guards to suit all types of woodlathes both new and existing installed within education workshops.

This lathe safety guard is a protective shield screen manufactured with a 5mm thick PETG panel and housed within a zinc coated metal frame.

Fitted as standard with a electrical interlock system it ensures the lathe cant be operated without the guard in position and is easily adjustable both horizontally and vertically to provide full coverage for both the main and bowl turning spindles.

### ACCESSORIES

- 2 x LED-lights with steel cover
- Back suction nozzle unit
- LED Kit (Wiring box for LED lights. Incl. electrical outlet, switch and 350 mA trafo.)

### AES PART CODE/ORDERING TABLE

Wood Lathe Safety Guard c/w micro switch for automatic shut down of machine when guard is opened during operation.	WE-LG03-002
--	-------------



AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT