

## WELD FILTER C20



### DESCRIPTION

WeldFilter mobile filter unit for light welding extraction applications.

- Easy to move and position
- Includes 3 meter (10 ft.) long Extraction Arm Original.
- Two cleanable filters with high filtration efficiency and easy to replace
- Service hour meter
- Alarm for low air flow (time to clean or replace the cartridge)



Accessories	Part no.
Spark protection, for mounting in the hood. To reduce risk of fire.	10551335
Replacement filter	Part no.
12m <sup>2</sup> spound bound polyester with PTFE lamination ≥ 99% efficiency for welding fume. Measured according to the test procedure in EN 15012-1.	12375379

Arm length m (ft.)	Arm Ø, mm (in.)	Max. airflow <sup>1)</sup> , m <sup>3</sup> /h (cfm)	Filter efficiency, %	Filter area, m <sup>2</sup> (sq. ft.)	Voltage, V/ electrical plug	Power, kW (Hp)	Frequency, Hz	Phase	Noice level dB (A)	Weight, kg (lbs)	Part no.
3 (10)	160 (6 ¼)	2 x 500-900 (300-530)	≥ 99	2 x 12 (125)	400/EUR <sup>2)</sup>	2.2 (3.0)	50	3	75	245 (540)	12621151
3 (10)	160 (6 ¼)	2 x 500-900 (300-530)	≥ 99	2 x 12 (125)	200/JP <sup>2)</sup>	2.2 (3.0)	50	3	75	245 (540)	12621251
3 (10)	160 (6 ¼)	2 x 500-900 (300-530)	≥ 99	2 x 12 (125)	200/JP <sup>2)</sup>	2.2 (3.0)	60	3	75	245 (540)	12621351

<sup>1)</sup> Maximum 2 x 1100 m<sup>3</sup>/h (650 cfm) without extraction arms.

<sup>2)</sup> Without male plug.

AES CAN PROVIDE THE GUIDANCE, DESIGN AND INSTALLATION OF YOUR PROJECT