

NEDERMAN FX2 ESD/EX ARM HOODS & ACCESSORIES



FX Combination Hood

Part No.	Description
70500244	FX-Combi hood-ESD/EX-D50/75/100. Black combi hood, made of conductive ABS plastic, is designed to capture low energy contaminants which is explosive or has a risk of electrostatic discharges. It can be attached directly on minihood, irrespective of arm size. The ergonomics of handle design on both sides of the hood make it easier to maneuver.

FX Dome Hood

Part No.	Description
70376983	FX-Dome hood-ESD/EX-50/75/100. Black dome hood, made of conductive ABS plastic, is designed to capture high dispersion contaminants, which is explosive or has a risk of electrostatic discharges. It can be attached directly on minihood, irrespective of arm size. The ergonomics of handle design on both sides of the hood make it easier to maneuver.

FX Metal Hood

Part No.	Description
70500544	FX-Metal hood-ESD/EX-D50/75/100. ESD conductive black metal hood, made of anodized aluminium, is designed to capture contaminants in high temperature, aggressive fume where corrosion resistance must be assured or explosive dust splatter. It can be attached directly on minihood, irrespective of arm size.

FX Flange Hood

Part No.	Description
70502944	FX-Flange hood-ESD/EX-D50/75/100. Black flange hood, made of conductive ABS plastic, is designed to maximise the capture zone without hinder objects on the bench or the user. It can be attached directly on minihood, irrespective of arm size.

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT

NEDERMAN FX2 ESD/EX ARM HOODS & ACCESSORIES

Part No.	Description	Image
70374600	FX-Cut2fit extension-L2200. Cut2fit extension could be at any length and should be assembled together with the classic bracket for mounting FX2 50/75/100 arms on the ceiling or wall.	
70377037	FX2-Duct connector-ESD/EX-D50. Conductive black duct connector to ease the coupling of 77mm Alu duct to external 80mm ductwork. Please note all arms are already supplied with a duct connector as standard.	
70377042	FX2-Bracket kit-D50/75/100-L500. Complete mounting kit, with the classic bracket, 500mm (19.68 inch) extension profile and associated parts, for mounting FX2 50/75/100 arms on the ceiling.	
70377044	FX2-Wall BRKT kit-Flat-L190-Black. Complete mounting kit, with flat wall bracke, 190 mm (7.48 inch) extension profile and associated parts, for mounting FX2 50/75/100 arms with 250 mm (9.84 inch) from the vertical centre line of the arm to the wall.	
70377045	FX2-Ceiling cover plate-PLUS, Cover false/dropped ceiling opening caused by tube.	
70377056	FX2-Al duct-L1000-D50toD77. Aluminium duct with 77mm (3 inch) diameter and 1000mm (39.37 inch) length is designed to replace vertical ventilation duct above the swivel of FX2 50 arm. This is a good looking alternative to standard, ventilation duct.	
70377057	FX2-Al duct-L2000-D50toD77. Aluminium duct with 77mm (3 inch) diameter and 2000 mm(78.74 inch) length is designed to replace vertical ventilation duct above the swivel of FX2 50 arm. This is a good looking alternative to standard, ventilation duct.	









AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT

NEDERMAN FX2 ESD/EX ARM HOODS & ACCESSORIES

Part No.	Description	Image
70377067	FX2-Hose support ring-D75. Place into the 75 mm (3 inch) hose to support the connection between the hose and the duct connector of the arm.	
70377101	FX-Hose-ESD-D75-L3000-Black-Flexible hose in black conductive PE with 75mm (3 inch) diameter and 3000 mm (118.11 inch) length. It shall be used with hose support ring to connect hose to arm.	
70501144	FX-Bracket kit-D50/75/100-L190	
70501244	FX-Classic bracket-D50/75/100. The classic bracket should be used together with Cut2fit extension profile for mounting FX2 50/75/100 arms on the ceiling, wall, floor or on top of other horizontal surface.	
70501344	FX-Cut2fit extension-L1100. Cut2fit extension could be cut at any length and should be assembled together with the classic bracket for mounting FX2 50/75/100 arms on the ceiling or wall.	
70501444	FX2-Bench bracket kit-D50/75/100 , Complete mounting kit for mounting FX2 50/75/100 arms on the bench edge.	
70502644	FX-Ceiling cover plate. Cover false/dropped ceiling openings caused by both extension profile and ducting.	

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT

NEDERMAN FX2 ESD/EX ARM HOODS & ACCESSORIES

Part No.	Description	Image
70377039	FX2-Duct connector-ESD/EX-D75	
70377041	FX2-Duct connector-ESD/EX-D100. Conductive black duct connector to ease the coupling of 100 mm (4 inch). Alu duct to external 125 mm (5 inch) ductwork. Please note all arms are already supplied with a duct connector as standard.	
70377058	FX2-Al duct-L1000-D75/100 to D100 Aluminium duct with 100 mm (4 inch) diameter and 1000 mm (39.37 inch) length is designed to replace vertical ventilation duct above the swivel of FX2 75/100 arm. This is a good looking alternative to standard, ventilation duct.	
70377059	FX2-Al duct-L2000-D75/100 to D100 Aluminium duct with 100 mm (4 inch) diameter and 2000 mm (78.74 inch) length is designed to replace vertical ventilation duct above the swivel of FX2 75/100 arm. This is a good looking alternative to standard, ventilation duct.	
70377068	FX2-Hose support ring-D100. Place into the 100 mm (4 inch) hose to support the connection between the hose and the duct connector of the arm. A must to connect the hose to arm.	
70377069	FX2-Hose support ring-D125. Place into the 125 mm (5 inch) hose to support the connection between the hose and the duct connector of the arm. A must to connect the hose to arm.	
70377102	FX-Hose-ESD-D100-L3000-Black-Flexible hose in black conductive PE with 100 mm (4 inch) diameter and 3000 mm (118.11 inch) length. It shall be used with hose support ring to connect hose to arm.	
70377103	FX-Hose-ESD-D125-L5000-Black - Flexible hose in black conductive PE with 125 mm (5 inch) diameter and 5000 mm (195.85 inch) length. It shall be used with hose support ring to connect hose to arm.	

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT