

TB LOW PROFILE BOOTHS



DESCRIPTION

Low Profile Booths provide protection for both the operator and the working environment by extracting the light airborne dusts generated by sanding, grinding and trimming processes.

The booths are available in three standard sizes: 1.8, 2.4 or 3.6 metres and are only 1.2 metres high which ensures that the operator can only work on the clean side of the booth.

The booths have recessed tops to allow clearance for overhead lifting of large work pieces, large work is normally carried out on the floor whilst intermediate work can be carried out on trestles or purpose built insertable benches.

PART CODE/ORDERING TABLE

Description	Part. No.
TB Booth 1.8 m	TB 1.8
TB Booth 2.4 m	TB 2.4
TB Booth 3.6 m	TB 3.6

SUPPLIED WITH

TB Booths do not have internal fans or filters, and are just used widely in conjunction with the LW22P wet exhaust units. This combination is mainly used to deal with hazardous sparks and dusts such as aluminium and titanium.

TECHNICAL SPECIFICATION

Model	Air Volume	Motor	Noise Level	Electrical Supply	Length	Width	Height
TB 1.8	7 600 m ³ /h	2 x 4 kW	78 dB(A)	415 V 3 ph.	1800 mm	1830 mm	122 mm
TB 2.4	11 400 m ³ /h	2 x 4 kW	78 dB(A)	415 V 3 ph.	2400 mm	1830 mm	122 mm
TB 3.6	15 200 m ³ /h	2 x 4 kW	80 dB(A)	415 V 3 ph.	3600 mm	1830 mm	122 mm

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT