

TRANSLAS 8XE MIG EXTRACTION TORCH - 300 AIR-COOLED



NOZZLES

- 14 mm Special

Where space is limited and fit is tight, this nozzle offers better access and more excellent shielding gas coverage to prevent porosity.

- 17 mm Special

For heavier thickness, high-current and high-deposition butt and lap joint applications, this nozzle offers more excellent shielding gas coverage to prevent porosity.



DESCRIPTION

The Translas 8XE MIG Extraction Torch integrates the most efficient fume extraction structure in the welding industry.

The torch comes with three different angles, 30°, 45° and straight. The 8XE MIG Extractor, combined with the ClearO2 W-series 100 and 200, captures up to 98% of welding fumes directly at the source.

The 8XE MIG Extractor provides the safest and most effective solution for welders and workers to breathe CLEAN AIR and better work environments.

TECHNICAL SPECIFICATION

Power Rating	
- Mixed Gas	300 AMP
- CO2	320 AMP
Duty Cycle	100 %
Angles	- 30° - 45° - Straight
Nozzles	- 14 mm - 17 mm

TORCH PROFILE



FEATURES

- Reduces welding fumes up to 98%
- Unique contact tip for manual fitting and durability
- Special design contact tip for longer lifetime
- Ergonomic ball socket 30° angle and 360° rotatable
- Two unique nozzle design 14 mm and 17 mm for optimal performance

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT

TRANSLAS 8XE MIG EXTRACTION TORCH - 300 AIR-COOLED

COMPLETE TORCHES

Part Code	Item
8XE3020301000	8XE Extractor 3 metre gas cooled - 45° (standard)
8XE3020401000	8XE Extractor 4 metre gas cooled - 45° (standard)
8XE3020501000	8XE Extractor 5 metre gas cooled - 45° (standard)
8XE3120301000	8XE Extractor 3 metre gas cooled - 30°
8XE3120401000	8XE Extractor 4 metre gas cooled - 30°
8XE3120501000	8XE Extractor 5 metre gas cooled - 30°

CONSUMABLES

Part Code	Item	
3937041	Nozzle conical 14mm special	
3937045	Nozzle conical 17mm special	
140110	Contact tip 8XE - 1.0	
1401101	Contact tip 8XE - 1.0 CuCrZr	
1401102	Contact tip 8XE - 1.0 Alu	
140112	Contact tip 8XE - 1.2	
1401121	Contact tip 8XE - 1.2 CuCrZr	
1401122	Contact tip 8XE - 1.2 Alu	
140116	Contact tip 8XE - 1.6	
1401161	Contact tip 8XE - 1.6 CuCrZr	
39327200	Tip Adaptor	
302535	STEEL Plastic coated liner red (2.0/4.5) 3 metre - for 1.0/1.2 mm steel wire	
302545		Plastic coated liner red (2.0/4.5) 4 metre - for 1.0/1.2 mm steel wire
302555		Plastic coated liner red (2.0/4.5) 5 metre - for 1.0/1.2 mm steel wire
303635		Plastic coated liner yellow (2.5/4.5) 3 metre - for 1.6 mm steel wire
303645		Plastic coated liner yellow (2.5/4.5) 4 metre - for 1.6 mm steel wire
303655		Plastic coated liner yellow (2.5/4.5) 5 metre - for 1.6 mm steel wire
302538	ALUMINIUM Teflon red (2.0/4.0) 3 metre - for 1.0-1.2 mm aluminium wire	
302548		Teflon red (2.0/4.0) 4 metre - for 1.0-1.2 mm aluminium wire
302558		Teflon red (2.0/4.0) 5 metre - for 1.0-1.2 mm aluminium wire
303638		Teflon yellow (2.7/4.7) 3 metre - for 1.6 mm aluminium wire
303648		Teflon yellow (2.7/4.7) 4 metre - for 1.6 mm aluminium wire
303658		Teflon yellow (2.7/4.7) 5 metre - for 1.6 mm aluminium wire
304830	STAINLESS STEEL Graphite liner black (2.0/4.0) 3 metre combiliner - for 1.0-1.2 mm	
304831		Graphite liner black (2.0/4.0) 4 metre combiliner - for 1.0-1.2 mm
304832		Graphite liner black (2.0/4.0) 5 metre combiliner - for 1.0-1.2 mm
3048351		Graphite liner black (2.3/4.7) 3 metre combiliner - for 1.6 mm
3048361		Graphite liner black (2.3/4.7) 4 metre combiliner - for 1.6 mm
3048371		Graphite liner black (2.3/4.7) 5 metre combiliner - for 1.6 mm

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT