

# TRANSLAS 8XE MINI MIG EXTRACTION TORCH - 250 AIR-COOLED



## NOZZLES

### - 12 mm

The nozzle offers slightly more comprehensive shielding gas coverage on medium-thickness materials in butt and fillet applications, and outside-corner joints.

### -14mm-Special

Where space is limited and fit is tight, this nozzle offers better access and more excellent shielding gas coverage to prevent porosity. This 14mm special nozzle is delivered as a standard on every extractor torch.



## DESCRIPTION

The Translas 8XE MINI MIG Extraction Torch integrates the most efficient fume extraction structure in the welding industry.

The torch comes with three different angles, 30°, 45° and straight. The 8XE MIG Extractor, combined with the ClearO2 W-series 100 and 200, captures up to 98% of welding fumes directly at the source.

The 8XE MIG Extractor provides the safest and most effective solution for welders and workers to breathe CLEAN AIR and better work environments.

## TECHNICAL SPECIFICATION

<b>Power Rating</b>	
- Mixed Gas	250 AMP
- CO2	280 AMP
Duty Cycle	100 %
Angles	- 30° - 45° - Straight
Nozzles	- 12 mm - 14 mm

## TORCH PROFILE



## FEATURES

- Reduces welding fumes up to 98%
- Unique contact tip for manual fitting and durability
- Special design contact tip for longer lifetime
- Ergonomic ball socket 30° angle and 360° rotatable
- Two unique nozzle design 12mm and 14mm for optimal performance and durability

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT

## TRANSLAS 8XE MINI MIG EXTRACTION TORCH - 250 AIR-COOLED

### COMPLETE TORCHES

Part Code	Item
8XE1000301000	8XE MINI Extractor 3 metre gas cooled - 45° (standard)
8XE1000401000	8XE MINI Extractor 4 metre gas cooled - 45° (standard)
8XE1000501000	8XE MINI Extractor 5 metre gas cooled - 45° (standard)
8XE1100301000	8XE MINI Extractor 3 metre gas cooled - 30°
8XE1100401000	8XE MINI Extractor 4 metre gas cooled - 30°
8XE1100501000	8XE MINI Extractor 5 metre gas cooled - 30°

### CONSUMABLES

Part Code	Item	
3937000	Nozzle conical 12mm	
3937001	Nozzle conical 14mm special	
3937002	Nozzle conical 14mm	
140108	Contact tip 8XE - 0.8	
140110	Contact tip 8XE - 1.0	
1401101	Contact tip 8XE - 1.0 CuCrZr	
1401102	Contact tip 8XE - 1.0 Alu	
140112	Contact tip 8XE - 1.2	
1401121	Contact tip 8XE - 1.2 CuCrZr	
1401122	Contact tip 8XE - 1.2 Alu	
39327100	Tip Adaptor	
301535	<b>STEEL</b> Plastic coated liner blue (1.5/4.5) 3 metre - for 0.8 mm steel wire	
301545		Plastic coated liner blue (1.5/4.5) 4 metre - for 0.8 mm steel wire
301555		Plastic coated liner blue (1.5/4.5) 5 metre - for 0.8 mm steel wire
302535	<b>STEEL</b> Plastic coated liner red (2.0/4.5) 3 metre - for 1.0/1.2 mm steel wire	
302545		Plastic coated liner red (2.0/4.5) 4 metre - for 1.0/1.2 mm steel wire
302555		Plastic coated liner red (2.0/4.5) 5 metre - for 1.0/1.2 mm steel wire
301538	<b>ALUMINIUM</b> Teflon liner blue (1.5/4.0) 3 metre - for 0.8 mm aluminium wire	
301548		Teflon liner blue (1.5/4.0) 4 metre - for 0.8 mm aluminium wire
301558		Teflon liner blue (1.5/4.0) 5 metre - for 0.8 mm aluminium wire
302538	<b>ALUMINIUM</b> Teflon liner red (2.0/4.0) 3 metre - for 1.0/1.2 mm aluminium wire	
302548		Teflon liner red (2.0/4.0) 4 metre - for 1.0/1.2 mm aluminium wire
302558		Teflon liner red (2.0/4.0) 5 metre - for 1.0/1.2 mm aluminium wire

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT