

## GEOVENT GEOFLEX STANDARD HOSE 10 M



### FEATURES

<b>Material</b>	PVC hose with aluminium foil, 5 layer laminate with steel spiral.
<b>Colour</b>	Black
<b>Length</b>	Standard 10 meters
<b>Temperature Resistance</b>	-40 °C to +140 °C
<b>Application</b>	Extraction of welding fumes, grinding, dust, vapours, etc.
<b>Properties</b>	Super light weight High flexibility Antistatic and spark-proof

### DESCRIPTION

The Geovent GeoFlex Standard ventilation hose for extraction of welding fumes, grinding dust, fumes, etc.

Made of PVC hose with an inner aluminium foil.

The GeoFlex Standard hose for the extraction of welding smoke, grinding dust, vapors etc.

The temperature range is -30 °C to +140 °C.

The GeoFlex Standard Hose is available in lengths of 10 m and in dimensions of Ø50 to Ø250 mm.

### TECHNICAL SPECIFICATION

Art. No.	Diam [mm]	Weight [kg/m]	Bend [mm]	Max. Ard. tryk [kPa]	Max. Air hast [m/s]
09-012	50	0.14	29	3	30
09-002	82	0.16	48	3	30
09-003	102	0.17	59	3	30
09-005	127	0.21	74	3	30
09-001	152	0.32	88	3	30
09-004	160	0.35	93	3	30
09-000	203	0.46	118	3	30
09-019	254	0.61	147	3	30

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT