

Dust and Fume Extraction

SA - FUNNEL SHAPED RUBBER NOZZLE WITH VICE GRIP





DESCRIPTION

The SA type nozzle is a soft rubber nozzle, supplied with or without a tight damper.

Available Ø100, Ø125 & Ø150 mm hose connection.

The SA nozzle is available with an automatic damper which opens the moment the nozzle is secured to the exhaust and begins the extraction of fumes. The nozzle is suitable for a wide range of vehicles, and due to the soft rubber material the risk of scratching the vehicle is minimised.

OPERATION

The Nozzle is capable of fitting on to nozzles of many sizes and secured with a vice grip.

The flexible nature of the rubber and secure vice grip connection allows the exhaust pipe to be sealed and the fumes can then be extracted safely.

The nozzle can be attached onto the exhaust directly and connected to a hose reel or channel duct system to achieve efficient and safe extraction.

AES can supply hose reels, channel ducting and other extraction options to suit the SA nozzle.

TECHNICAL SPECIFICATION/AES ORDERING TABLE

Part No.	Description	Hose Connection	Exhaust	Weight	AES Part Code
06-163	SA Ø100/150	Ø100 mm	Ø150 mm	1.45 kg	EA-NZ04-001
06-163A	SA Ø100/150, w. tight damper	Ø100 mm	Ø150 mm	2 kg	EA-NZ04-002
06-164	SA Ø125/190	Ø125 mm	Ø190 mm	2.1 kg	EA-NZ04-003
06-164A	SA Ø125/190, w. tight damper	Ø125 mm	Ø190 mm	3.35 kg	EA-NZ04-004
06-165	SA Ø150/190	Ø150 mm	Ø190 mm	1.9 kg	EA-NZ04-005
06-165A	SA Ø150/190, w. tight damper	Ø150 mm	Ø190 mm	3.15 kg	EA-NZ04-006
06-160	SA Ø100/150, w/automatic damper	Ø100 mm	Ø150 mm	2.05 kg	EA-NZ04-007
06-161	SA Ø125/190, w/automatic damper	Ø125 mm	Ø190 mm	3.05 kg	EA-NZ04-008
06-162	SA Ø150/190, w/automatic damper	Ø150 mm	Ø190 mm	2.85 kg	EA-NZ04-009

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT