

Rev. 1 - January 2020

Dust and Fume Extraction

NEDERMAN COMPRESSIBLE RUBBER NOZZLE



DESCRIPTION

The Nederman compressible rubber nozzle gives users the ability to attach the nozzle with more room for adjustments.

The compressible rubber hood allows the nozzle to be attached at a range of angles, helpful if your extraction hose is mounted from above.

Ideally suited for heavy vehicles.

Available in Ø150 & Ø200 mm hose connection.

Available in two sizes to fit exhausts up to 180 or 230 mm.



OPERATION

The Compressible Rubber Nozzle attaches to the exhaust tip via a clamp system.

The compressible material surroundings the exhaust tip allows the nozzle to be attached at a range of angles.

The nozzle can be attached onto the exhaust directly and connected to a hose reel or channel duct system to achieve efficient and safe extraction.

AES can supply hose reels, channel ducting and other extraction options to suit the nozzle.

TECHNICAL SPECIFICATION

Part No.	Description	Exhaust	Hose Connection
20806961	Nederman Rubber Nozzle, Round with Swivel, Compressible, 150 mm	Ø180 mm	Ø150 mm
20807061	Nederman Rubber Nozzle, Round with Swivel, Compressible, 200 mm	Ø230 mm	Ø200 mm
Other Rubber Nozzle			
20808861	Rubber Nozzle for Vertical Stack		

AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT