

## F Save

F Save connects directly to your machine tool coolant pumps to automatically switch your Filtermist oil mist collector on and off based on your production activity.

### Product Specifications and Dimensions

	F Save Hub	F Save Sensor
Part number	20-211-30-069	20-211-30-070
Description	Designed to be installed between the machine isolator and the Filtermist unit. One free sensor is included with every hub.	Additional sensors are available for machines with multiple coolant pumps. The sensors easily clips to the coolant pumps.
Dimensions	292 x 220 x 85mm	65 x 38 x 24mm
Weight (Kg)	1.35	0.15
Wiring	N/A	10m cable



F Save Hub



F Save Sensor

### Equipment Compatibility

F Save is compatible with all current Filtermist units and older models. The hub can be mounted to a post, floor stand or wall - screws are included with every hub installation kit.

### Power Specifications

Power Source	3 Phase or Single Phase
Voltage Rating	200V - 480V
Frequencies	50/60Hz
Maximum Current	10A (Max continuous operating current)
Earthing	Earthed via the power supply (3-wire, 3P+PE)
Sensor Type	Magnetic field sensor (non-contact)
Enclosure Material	ABS Fire Retardant Plastic



Ports for four sensors enable the F Save to be connected to up to four coolant pumps.