

Hose & Cable Reels

NEDERMAN 889 HOSE REEL ATEX



DESCRIPTION

The Nederman 889 ATEX is a medium-sized hose reel for industrial use. All major components are made of stainless steel or electrically conductive composite material, required for chemically aggressive and explosive environments. The design of the reels makes it easy to keep clean for installation in ATEX zones 1, 2, 21 and 22 in accordance with ATEX2014/34/EC, Equipment group II, Category 2G D.


FEATURES

- Unique design makes easy cleaning
- Up to 15 m (49 ft.) hose capacity
- Meets international hygienic requirement
- ATEX approved

TECHNICAL SPECIFICATIONS

| Connection Hose Length | 1 m |
|----------------------------|-----------------------|
| Type of hose | М |
| Media | Compressed Air, Water |
| Colour | Stainless |
| Distribution hose length | 15 m |
| Diameter, connection hose | Ø12.5 mm |
| Distribution hose diameter | Ø12.5 mm |
| Max working pressure | 2 Mpa |
| Max hose length | 2 m |
| Corrosion resistance | Stainless steel |
| Electric/Spring driven | Spring |

DIMENSIONS



| Delivered with hose | Weight | Part Codes |
|---------------------|--------|------------|
| Yes | 18 kg | 30804689 |
| No | 14 kg | 30804789 |

| Hose Type | Specification | Temperature range, °C |
|---|--|--|
| М | Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive. | -30 - +80 |
| Hose fitting on free hose end, inlet hose | Hose connection on reel, distribution hose | Hose connection on reel, inlet hose |
| | | |



AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT