

NEDERMAN PROTECTION CURTAINS



WELDING CURTAIN PART CODES

Item	Part Codes
Protection curtain transparent yellow 1,4 x 1,8 m, h= 1800 mm	60313524*
Protection curtain transparent yellow 1,4 x 2,8 m, h= 2800 mm	60313526*
Protection curtain transparent yellow 1,4 x 2,4 m, h= 2400 mm	60313525*
Protection curtain transparent clear 1,4 x 1,8 m, h= 1800 mm	60313624*
Protection curtain transparent clear 1,4 x 2,4 m, h= 2400 mm	60313625*
Protection curtain transparent clear 1,4 x 2,8 m, h= 2800 mm	60313626*

*Total width of curtains shall be 10% longer than total required screening length.

DESCRIPTION

Standard sized curtains (see below) provided with 50 mm welded seam all around and with snap-fasteners on both sides for joining to obtain total desired width.

Supplied with reinforced holes in the upper edge and steel suspension rings. All standard curtains are made of pliable self extinguishing PVC material with flash point 320-390°C.

Width: 1400 mm, Thickness: 0.40-0.50 mm.

The Nederman Protection Curtains Transparent Yellow and Transparent Clear are used for glare, splatter, grinding, dust etc. but are not aimed for welding.

ADDITIONAL IMAGE



ACCESSORIES

Accessory	Part No.
Nederman Curtain Ring PVC 45mm 7-pack	60344976
Nederman Curtain Steel Ring Ø40 mm 7-pack	60064850*

*Included when ordering new curtains.



AES OFFER INSTALLATION AND SERVICE SUPPORT FOR ALL EQUIPMENT